

ALUMINIUM-WINKELPROFILE



AlMgSi0,5 F 22, DIN 1725/1748/1771, (EN 573-3/755-1, 2)

Winkel gleichschenkelig, gepresst, warm ausgehärtet, in Herstellungslängen von 6 m



AlMgSi0,5
EN AW-
6060 T66
W.-Nr.
3.3206

Abmessungen mm
B x L x S F 22
Gewicht ca. kg/m


10 x 10 x 2,0	0,100
12 x 12 x 2,0	0,120
15 x 15 x 2,0	0,151
15 x 15 x 3,0	0,218
20 x 20 x 1,5	0,156
20 x 20 x 2,0	0,205
20 x 20 x 3,0	0,299
20 x 20 x 4,0	0,390
25 x 25 x 2,0	0,259
25 x 25 x 3,0	0,380
25 x 25 x 4,0	0,500
30 x 30 x 2,0	0,313
30 x 30 x 3,0	0,465
30 x 30 x 4,0	0,604
30 x 30 x 5,0	0,742
35 x 35 x 2,0	0,370
35 x 35 x 3,0	0,545
35 x 35 x 4,0	0,718
35 x 35 x 5,0	0,878



AlMgSi0,5
EN AW-
6060 T66
W.-Nr.
3.3206

Abmessungen mm
B x L x S F 22
Gewicht ca. kg/m

40 x 40 x 2,0	0,423
40 x 40 x 3,0	0,624
40 x 40 x 4,0	0,824
40 x 40 x 5,0	1,015
40 x 40 x 6,0	1,262
45 x 45 x 4,0	0,930
45 x 45 x 5,0	1,170
50 x 50 x 2,0	0,531
50 x 50 x 3,0	0,785
50 x 50 x 4,0	1,040
50 x 50 x 5,0	1,290
50 x 50 x 6,0	1,555
50 x 50 x 8,0	1,990
50 x 50 x 10,0	2,430
60 x 60 x 2,0	0,637
60 x 60 x 3,0	0,950
60 x 60 x 4,0	1,252
60 x 60 x 5,0	1,552
60 x 60 x 6,0	1,850
60 x 60 x 8,0	2,419
60 x 60 x 10,0	2,970



AlMgSi0,5
EN AW-
6060 T66
W.-Nr.
3.3206

Abmessungen mm
B x L x S F 22
Gewicht ca. kg/m

70 x 70 x 5,0	1,823
70 x 70 x 6,0	2,170
70 x 70 x 7,0	2,514
80 x 80 x 3,0	1,275
80 x 80 x 4,0	1,685
80 x 80 x 5,0	2,135
80 x 80 x 6,0	2,500
80 x 80 x 8,0	3,283
80 x 80 x 10,0	4,120
90 x 90 x 10,0	4,590
100 x 100 x 4,0	2,117
100 x 100 x 6,0	3,143
100 x 100 x 8,0	4,150
100 x 100 x 10,0	5,130
120 x 120 x 8,0	5,011
120 x 120 x 12,0	7,387