


AlMgSi0,5 F 22, DIN 1725/1748/1771, (EN 573-3/755-1, 2)


Winkel ungleichschenkelig, gepresst, warm ausgehärtet, in Herstellungslängen von 6 m



AlMgSi0,5
EN AW-
6060 T66
W.-Nr.
3.3206

Abmessungen mm
B x L x S
F 22
Gewicht ca. kg/m


15 x 10 x 2,0	0,124
20 x 10 x 2,0	1,151
20 x 10 x 3,0	0,219
20 x 15 x 2,0	0,178
20 x 15 x 3,0	0,260
25 x 10 x 2,0	0,180
25 x 10 x 3,0	0,270
25 x 15 x 2,0	0,205
25 x 15 x 3,0	0,300
25 x 20 x 2,0	0,235
25 x 20 x 3,0	0,340
30 x 10 x 2,0	0,205
30 x 15 x 2,0	0,232
30 x 15 x 3,0	0,340
30 x 20 x 2,0	0,260
30 x 20 x 3,0	0,380
30 x 20 x 4,0	0,500
30 x 25 x 2,0	0,286
30 x 25 x 3,0	0,425
35 x 20 x 3,0	0,421
35 x 25 x 2,0	0,315
35 x 25 x 3,0	0,480
35 x 30 x 3,0	0,502
40 x 10 x 2,0	0,260
40 x 15 x 2,0	0,290
40 x 20 x 2,0	0,315
40 x 20 x 3,0	0,462
40 x 20 x 4,0	0,605
40 x 20 x 5,0	0,743
40 x 25 x 2,0	0,340
40 x 25 x 3,0	0,505
40 x 25 x 4,0	0,680
40 x 30 x 2,0	0,370
40 x 30 x 3,0	0,545
40 x 30 x 4,0	0,713
40 x 30 x 5,0	0,920
45 x 20 x 3,0	0,502
45 x 30 x 3,0	0,583
50 x 15 x 2,0	0,340
50 x 15 x 3,0	0,515



AlMgSi0,5
EN AW-
6060 T66
W.-Nr.
3.3206

Abmessungen mm
B x L x S
F 22
Gewicht ca. kg/m

50 x 20 x 2,0	0,370
50 x 20 x 3,0	0,545
50 x 20 x 4,0	0,713
50 x 25 x 2,0	0,395
50 x 25 x 3,0	0,585
50 x 25 x 4,0	0,766
50 x 25 x 5,0	0,955
50 x 30 x 2,0	0,426
50 x 30 x 3,0	0,625
50 x 30 x 4,0	0,821
50 x 30 x 5,0	1,027
50 x 35 x 4,0	0,895
50 x 40 x 2,0	0,475
50 x 40 x 3,0	0,704
50 x 40 x 4,0	0,929
50 x 40 x 5,0	1,175
60 x 10 x 2,0	0,367
60 x 20 x 2,0	0,425
60 x 20 x 3,0	0,625
60 x 25 x 2,0	0,448
60 x 25 x 3,0	0,664
60 x 30 x 2,0	0,475
60 x 30 x 3,0	0,704
60 x 30 x 4,0	0,928
60 x 30 x 5,0	1,163
60 x 40 x 2,0	0,530
60 x 40 x 3,0	0,785
60 x 40 x 4,0	1,040
60 x 40 x 5,0	1,285
60 x 40 x 6,0	1,523
70 x 15 x 2,0	0,448
70 x 20 x 2,0	0,475
70 x 30 x 3,0	0,800
70 x 30 x 5,0	1,283
70 x 50 x 5,0	1,620
75 x 50 x 5,0	1,680
75 x 50 x 7,0	2,340
80 x 15 x 2,0	0,502
80 x 20 x 2,0	0,530
80 x 30 x 3,0	0,900
80 x 40 x 2,0	0,655
80 x 40 x 3,0	0,950
80 x 40 x 4,0	1,253



AlMgSi0,5
EN AW-
6060 T66
W.-Nr.
3.3206

Abmessungen mm
B x L x S
F 22
Gewicht ca. kg/m

80 x 40 x 5,0	1,553
80 x 40 x 6,0	1,850
80 x 50 x 4,0	1,361
80 x 50 x 5,0	1,688
80 x 60 x 4,0	1,470
80 x 60 x 6,0	2,171
100 x 20 x 2,0	0,637
100 x 30 x 3,0	1,029
100 x 40 x 3,0	1,110
100 x 40 x 4,0	1,470
100 x 50 x 3,0	1,200
100 x 50 x 5,0	1,958
100 x 50 x 6,0	2,332
100 x 50 x 10,0	3,920
100 x 60 x 6,0	2,495
100 x 80 x 3,0	2,819
100 x 80 x 8,0	3,715
120 x 40 x 4,0	1,685
120 x 50 x 5,0	2,228
120 x 60 x 6,0	2,820
120 x 60 x 8,0	3,780
120 x 80 x 8,0	4,145
120 x 80 x 10,0	5,130
130 x 30 x 3,0	1,270
140 x 40 x 3,0	1,434
140 x 40 x 6,0	2,819
150 x 50 x 4,0	2,120
150 x 75 x 8,0	4,687
150 x 75 x 10,0	6,100
150 x 100 x 5,0	3,310
150 x 100 x 10,0	6,750
160 x 40 x 4,0	2,117
180 x 80 x 10,0	6,750
180 x 150 x 6,0	5,249
200 x 100 x 10,0	7,830
200 x 100 x 15,0	11,543