

MESSING-STANGEN



CuZn39Pb3, (Ms 58), gezogen bzw. gepresst in Bohr- und Drehqualität, in Herstellungslängen von 3 m,
Werkstoff-Nr. CW 614 N (2.0401)



MESSING-RUNDSTANGEN

DIN 17660 / 1782 / 17672 (EN 12165 / 12163 / 12164 / 12167)

Abmessungen mm D	Gewicht ca. kg/m	Abmessungen mm D	Gewicht ca. kg/m	Abmessungen mm D	Gewicht ca. kg/m
3,0	0,06	23,0	3,55	50,0	16,69
4,0	0,11	24,0	3,84	52,0	18,05
5,0	0,17	25,0	4,16	55,0	20,20
6,0	0,24	26,0	4,51	56,0	20,95
7,0	0,33	27,0	4,88	60,0	24,03
8,0	0,43	28,0	5,32	65,0	28,20
9,0	0,54	29,0	5,61	70,0	32,71
10,0	0,67	30,0	6,01	75,0	37,55
11,0	0,81	31,0	6,49	80,0	42,73
12,0	0,96	32,0	6,84	85,0	48,24
13,0	1,13	33,0	7,35	90,0	54,08
14,0	1,31	35,0	8,19	95,0	60,22
15,0	1,50	36,0	9,65	100,0	66,76
16,0	1,73	37,0	9,15	110,0	80,80
17,0	1,95	38,0	9,64	120,0	96,10
18,0	2,16	40,0	10,68	130,0	112,80
19,0	2,41	42,0	11,77	150,0	150,20
20,0	2,67	45,0	13,51	160,0	170,90
21,0	2,94	46,0	14,13	200,0	267,10
22,0	3,23	48,0	15,38	250,0	417,25